Tube Style LED Tubular Light

- PC IK10/PMMA IK08
- Anti-ammonia
- Chemical resistant
- 130lm/W
- Against water pressure of 100bar(1450psi) and temperature of 80℃

Tube Style LED Tubular Light

Features

- IP67 & IP69K
- PMMA IK08 / PC IK10
- Against water pressure of 100bar(1450psi) and temperature of 80℃
- System efficiency up to 130lm/W
- High CRI >80
- Environmentally friendly, no mercury, No UV, No IR
- Wide beam angle 120°
- Energy Efficiency Grade: A+
- Quick Start instant 100% luminous flux
- 5 Year Warranty on complete fixture. (LED's, Driver, & Housing)
- Certificate: CE, RoHs Certified
- Surface Mount or Suspended

CE CB IK10 RoHS IP69K 130lm/W 5 Year WARRANTY

AC200-240V -20~+40 IK10 RG 0/1 50.000H Dimmable Emergency DLG

Applications

- Car parking Lighting
- School Lighting
- Workshops
- Supermarket
- Warehouse
- Storage

120°

TUBU

20W/40W/50W/60W

Single installation

Linkable Installation

Tube Style LED Tubular Light

Specifications

Product Code		TBL92F-20W-T	TBL94F-40W-T	TBL95F-50W-T	TBL95F-60W-T
Power		20W	40W	50W	60W
Input Voltage		200-240VAC/100-277VAC (50/60HZ)			
Input Current		0.09A@220VAC	0.19A@220VAC	0.23A@220VAC	0.28A@220VAC
PF		0.90@220VAC			
Dimming Option		0-10V/Dali			
CCT		3000K/4000K/5000K/6000K			
Ra > 80	**Luminous Flux**	2600Lm±5%	5200Lm±5%	6500Lm±5%	7800Lm±5%
	Efficiency	130Lm/W±5%			
LED Brand		Lumileds/Hongli			
Beam Angle		120°			
Operation Temp		-20℃~+40℃			
Storage Temp		-20℃~+60℃			
Life Span		Ta 40℃ L70>54000Hours			
IP Class		IP67&IP69K			
IK Class		PMMA IK08/PC IK10			
Certificate		CE, RoHs, CB, IK10, IP69K, ENEC			
Lamp Body Color		Milky PC/PMMA Housing & 304/316 Stainless Steel End Caps			
Product Size (mm)		∅75*552	∅75*1152	∅75*1452	∅75*1452
Packing Size (mm)		730*260*260	1330*260*180	1630*260*180	1630*260*180
Quantity/carton		9PCS	6PCS	6PCS	6PCS
Gross weight (kg) ±0.3		12	15	23	23
Installation mode		Surface Mount/Suspension Mount			